

Three degrees of terratrak®

The ultimate protection from very heavy loads

All three types of terratrak® tiles are fully interlocking, therefore different tiles can be used in areas requiring varying degrees of protection. The unique design ensures that there is negligible damage to the turf, & the 100mm (4 inch) overlap acts as a barrier to stop liquids from penetrating to the grass.



terratrak plus®

Specifically developed for use during concert load-in and load-out, **terratrak plus®** has proven itself as the product of choice for Stadiums and Arenas the World over, allowing them to host high profile Concerts and Events in quick succession with sporting fixtures, without risk to their playing surface.

For years Promoters have been looking for a product which would enable them to bring 100+ tonne cranes, forklifts and trucks onto the stadium field without causing significant damage.

For ease of use, flexibility and protection of the turf surface, **terratrak plus®**, is superior to any other product on the market.



Top side showing vertical camlock

Inside of top panel showing grid

Inside of bottom panel showing grid

Underside of assembled tile



terratrak-WF® (With Feet)

Designed for the protection of 'quality natural turf' when continuous photosynthesis and air circulation are required. This ensures good grass colour and health, when covered for a number of days for non-sporting events.

terratrak-WF® is fitted with 25 x patented circular feet that extend 10mm from the underside of the tile to create an air flow, which reduces disease.



The inventive circular ribbing geometry of terratrak® provides unparalleled strength with light weight, giving the fastest laying times of any product. Two people lay a panel of 4 tiles of terratrak-NF® or terratrak-WF® at one time, covering 4.84m² (52ft²).



terratrak-NF® (No Feet)

For artificial turf when superior strength is required, **terratrak-NF®** is the optimum solution.

The circular ribs spread the load evenly and any marks are easily removed with light brushing.

Price DOES Matter! The Strongest, & Most Cost Effective Systems Available – for EVERY type of event!

terrtrak® - 3 options - specifications:

Dimensions	Physical size: 1.21m (4') x 1.21m (4') x 38 mm (1½"). Prior to shipping terrtrak-plus® tiles are bolted in 2s. terrtrak-NF® & terrtrak-WF® are bolted in panels of 4. The bolted panels are shipped on pallets. Each tile has a "Usable" top surface when fitted of 1.21m ² (13.02ft ²), meaning a panel of 4 measures 4.84m ² (52.ft ²) & a panel of 2 is 2.42m ² (26ft ²)
Weight	terrtrak-plus® 23kgs per tile (51lbs per tile) or 46kgs per panel of 2 (101lbs) terrtrak-WF® 13kgs per tile (29lbs per tile) or 52kgs per panel of 4 (116lbs) terrtrak-NF® 12kgs per tile (26.4lbs per tile) or 48kgs per panel of 4 (106lbs)
Material	Virgin High Density, Polyethylene with UV stabiliser: 30 year warranty against UV degradation
Method of Manufacture	Structural foam Injection moulded using a blowing agent, which produces an engineering foam moulding with strength enhancing cellular core
Temperature Range	-20°C to 45°C (-4°F to 113°F)
Static Loading	terrtrak plus® Point load 20mm diameter = 1,173kgs - 1" square = 5,308lbs Spread load 164kN /150mm sq 7,288kN / m ² - 152,232lbs / ft ² 1,370,090lbs /yd ² terrtrak-NF® & terrtrak-WF® Point load 20mm diameter = 560kgs - 1" square = 2,813lbs Spread load 88kN /150mm sq 3,910kN / m ² - 80,682lbs / ft ² 726,147lbs /yd ²
Fire Requirements	UL94 HB
Colours	Translucent natural material, which allows the passage of light, allowing photosynthesis to continue whilst grass is covered. Colour options are available for artificial turf.
Cleaning	High pressure water spray washer
Warranty/ Life Expectancy	terrtrak plus® : 3 year Guarantee. Realistic life expectancy of c. 10 years. terrtrak-NF® & terrtrak-WF® : Guaranteed for 5 years but has a realistic life expectancy of c. 20 years
Slip Resistance	Integral slip-resistant surface.



T: +44 (0)1332 812813 E: terraplas@checkers-safety.com

Checkers Safety Group UK Ltd t/a Terraplas
The Barn, Hall Farm House, High Street, Castle Donington,
Derby, DE74 2PP UK
Tel: +44(0)1332 812813 Fax: +44(0)1332 853410

