




World's No.1 for *Turf Protection*



terraplas[®] HD – Fully driveable version of the Original **terraplas[®]** - both products lock directly to each other

terraplas-HD[®] is a version of **terraplas[®]** – the product that pioneered turf protection back in 1991. It locks directly to the standard terraplas (with or without feet) to form a monolithic floor.



terrapias-HD®



The fact that both versions of terrapias® lock together seamlessly creates a consistent, flat surface for patrons to gain access to the seating area of a stadium concert.



terrapias-HD® is assembled in single tiles and 2s, so that it can be placed on the warning track of an MLB Stadium like Great American Ballpark in Cincinnati (as shown in the pictures on this page).

It can also be used on any other stadium/arena surface to allow access for heavy equipment, before being transitioned to patron access flooring that can be left in place for a longer period of time.

The use of terrapias-HD® allows heavy vehicle access, making the install and removal cycle much faster for the production team, and certainly better in every way for the turf management staff.




Every terrapias® system that has been purchased since 1991 is still in use today!!

This incredible proven lifespan means that it is vital for those Clients to be able to keep up with modern stadium requirements, that are different in many ways to those that were applicable nearly 30 years ago.

The exciting development of terrapias® since 1991 is another demonstration of how Terrapias [*the Company*] is pro-active in addressing the needs of Stadiums & Arenas Worldwide.

Tiles with the recently implemented integral anti-slip top surface lock directly with the original painted stripe tiles.

The extremely strong design of terrapias®HD means that all 3 versions of **terrapias®** lock seamlessly to each other, delivering continuity across the brand. For synthetic turf/warning tracks etc, terrapias®HD is available in gray color (known as terrapias®HDID - *Heavy Duty InDoor*)



The infills are manufactured from the same HDPE material as the main tile.

The base is completely flat

terrapias-HD® Top Surface

The top surface of terrapias-HD has no holes, which differentiates it from regular terrapias

terrapias-HD® Bases are completely FLAT

terrapias-HD® Infill Structure

The infill panel has a completely flat base and incorporates a moulded insert pattern that best makes use of the internal space available, optimising the product strength and stability.



Close-up of Hook connector formed in the flat baseplate. This design adds strength to the joint and controls lateral twisting under the duress of vehicle motion.




Close-up of the steel pin & Rclip, which hold the tiles securely together in their pre-assembled panel format.

terraplas-HD® - specifications

Internationally acknowledged as the best systems available for turf protection, **MOST** of the World's Multi-use National Stadiums have purchased Terraplas products! Many more regularly rent them!




Dimensions	1m (3'3") x 1m (3'3") x 64mm (2½") Pinned as panels of 2 (measuring 2m x 1m / 6'6" x 3'3") prior to leaving the factory and loaded onto timber pallets as 2 x sets of 2 per row.
Weight	21kgs per m ² / 46lbs per tile)
Material	High molecular weight, Virgin high density, polyethylene NO FILLERS. with UV stabiliser – Translucent version guaranteed against UV degradation for 30 years!
Method of Manufacture	Structural Foam Injection moulded
Temperature Range	-20 degrees C to 50 degrees C (-4 degrees F to 122 degrees F)
Loading (Static) 676psi	Point load: 682kgs per 20mm diameter Spread load: 475,000kgs /475 tonnes per m ²
Fire Requirements	UL94HB
Color	Translucent natural material, which allows the best passage of light, ensuring grass growth – without yellowing Gray colour is available without breathing holes for use on synthetic turf./ warning track & other non-grass surfaces
Cleaning	High pressure hot or cold water spray washer / steam cleaner
Life Expectancy	Guaranteed for 10 years with a life expectancy of c. 30 years – based on actual proven lifespan of original terraplas® tiles.
Applications	Drivable with small cranes and forklifts. All vehicles MUST have pneumatic tyres. Temporary access to cover natural/synthetic turf for all types of special events – locks directly to terraplas® pedestrian turf protection tiles.
Slip Resistance	Highest rated integral anti-slip top surface



terraplas®

ADA/DDA ACCESS RAMPS

terraplas edge ramps are available that allow easy access for the disabled



These access ramps conform with international ADA/DDA requirements. They are manufactured to order.



World's No.1 for *Turf* Protection

For Further information contact:

Michael Beane

Director of Sales for The Americas

Terraplas North America

1106 W. Highway 31

75662 Kilgore

Texas

Ph: **903 983 2009**

Cell: **214 704 1090**

Email: **TheAmericas@terraplas.com**

Terraplas is a trading division of Hughes Safety Showers Ltd., part of the Justrite Safety Group.

www.terraplas.com